

HTML tags supported by HTMLToWord



HTMLToWord is an open source project from SoftArtisans. It can be downloaded from [SourceForge.net](https://sourceforge.net/projects/htmltoword/).

The following table lists the HTML tags that HTMLToWord explicitly supports.

The contents of HTML tags not listed in the table below (or custom XHTML tags in your document) will be inserted into the document as text. You can control this default behavior by setting the `AcceptUnknownTags` and `IncludeContentsOfUnknownTags` properties found in the `InsertHTMLProperties` property container and by implementing the [InsertDelegate](#) and [FormatDelegate](#) delegate methods.

HTML Tag	Description	Support Level
a	Inserts a hyperlink. Supported: HTTP-protocol hrefs Unsupported: https, mailto or ftp protocols in the href attribute and the name attribute.	Partial
b	Renders the text as bold.	Full
blockquote	Offsets text and narrows the left and right margins.	Full
br	Insert a line break.	Full
code	Renders the text in-line with a mono-spaced font.	Full
del	Renders text as strike-through. Supported: In-line elements. Unsupported: Block-level elements.	Partial
div	Inserts an unordered list into the document. (Note, this tag is deprecated as of HTML 4.01.)	Full
div	Mimics HTML by separating content from surrounding text. Unsupported: Does not support any attributes.	Partial
em	Renders the text as italics.	Full
font	Changes the font face, font size and/or font color. Size can be either absolute or relative. If given a comma-separated list of faces, uses the first face only. Color can be either a name or an HTML code, such as #FFFFFF for white.	Full
h1 . . . h6	Applies styles corresponding to Microsoft Word styles H1 through H6. Supported: Heading levels 1-6. Unsupported: Align attribute.	Partial
i	Italicize text.	Full

img	<p>Inserts an image in-line with the text. Relies on the GetImageDelegate method to retrieve the actual data bits of the image.</p> <p>Supported: In-line images. Height and width attributes as absolute pixel sizes.</p> <p>Unsupported: Floating or absolutely positioned images. Height and width specified as percentage, usemap attribute.</p>	Partial
ins	<p>Renders text as underlined.</p> <p>Supported: In-line elements.</p> <p>Unsupported: Block-level elements.</p>	Partial
li	<p>Creates a new item in the enclosing list.</p> <p>Unsupported: Attributes.</p>	Partial
menu	<p>Inserts an unordered list into the document. (Note, this tag is deprecated as of HTML 4.01.)</p>	Full
ol	<p>Ordered (numbered) list.</p> <p>Unsupported: Attributes.</p>	Partial
p	<p>Paragraph. The align attribute is supported.</p>	Full
pre	<p>Renders text in a mono-spaced font. Offsets block of text from surrounding text with an extra blank line before and after.</p> <p>Unsupported: The width attribute is ignored.</p>	Partial
s	<p>Renders text as strikethrough.</p>	Full
span	<p>Used to specify characteristics for a section of text with a block.</p>	Full
strike	<p>Renders text as strikethrough.</p>	Full
strong	<p>Renders text as bold.</p>	Full
style	<p>HTMLToWord does not parse the style tag; however, users can parse a style using a delegate method.</p> <p>Supported: User-supplied delegate method to handle styles.</p> <p>Unsupported: Automatic parsing of styles.</p>	Partial
sub	<p>Renders text as subscript</p>	Full
sup	<p>Renders text as superscript</p>	Full
table	<p>Inserts a table into the document. Nested tables are supported.</p> <p>Supported: bgcolor, border, cellpadding, cellspacing, frame, rules, and width attributes. Cellpadding and cellspacing attributes with absolute size values.</p> <p>Unsupported: Cellpadding and cellspacing attributes with percentage values.</p>	Partial

tbody	<p>Body of a table.</p> <p>Supported: tbody tags within the XHTML to denote the start of the body of the table.</p> <p>Unsupported: Cell alignment attributes: align, char, charoff and valign.</p>	Partial
td	<p>Specifies the contents of a table cell.</p> <p>Supported: The colspan, rowspan, align, valign, and bgcolor attributes.</p> <p>Unsupported: The abbr, axis, headers, scope, nowrap, width, height, char and charoff attributes.</p>	Partial
tr	Table row.	Full
tt	Renders text in a serified, mono-spaced font (Courier New).	Full
u	Renders text as underlined.	Full
ul	<p>Unordered (bulleted) list.</p> <p>Unsupported: Attributes.</p>	Partial