

WordTemplate.SetDataSource(System.Collections.IDictionary)

Description

Sets a template's main document data source to an [IDictionary](#) collection. An IDictionary represents a collection of key-and-value pairs.

C#

```
public void SetDataSource(System.Collections.IDictionary dataSource)
```

vb.net

```
Public Sub SetDataSource(ByVal dataSource As System.Collections.IDictionary)
```

Parameters

dataSource

An IDictionary collection of key-and-value pairs.

Exceptions

ArgumentNullException

[Save](#) will throw this exception if null (C#) or Nothing (VB.NET) is passed to the method.

ArgumentException

Remarks

Each merge field in a WordWriter template must bind to a data source field/value pair. The number of merge fields in the main template document (the part of the document that is not within a repeat block) may not exceed the number of values in the data source defined by [SetDataSource](#). However, the number of values in the data source may be greater than the number of merge fields in the main template document.

Do not call this method more than once for a single instance of [WordTemplate](#). To set multiple main document data sources, use the following methods:

[SetDataSource\(Object\(\), String\(\), String\)](#)

[SetDataSource\(System.Data.DataSet, String\)](#)

[SetDataSource\(System.Data.DataTable, String\)](#)

[SetDataSource\(System.Data.IDataReader, String\)](#)

Examples

C#

```
wTempl.SetDataSource(coll);
```

vb.net

```
wTempl.SetDataSource(coll)
```