

ExcelTemplate.BindRowData(System.Data.DataSet, String, DataBindingProperties)

Description

Sets a DataSet as a data source to bind to a row in the template. This method will import only the first row of the first DataTable of the DataSet. You must insert a datamarker into the template for each column of data you want shown.

C#

```
public void BindRowData(System.Data.DataSet dataSource, System.String dataSourceName, DataBindingProperties property)
```

vb.net

```
Public Sub BindRowData(ByVal dataSource As System.Data.DataSet, ByVal dataSourceName As String, ByVal [property] As DataBindingProperties)
```

Parameters

source

The DataSet to use as the data source.

dataSourceName

The name of the data marker at which to insert the values imported from the data source. For example, to bind a data source to the data marker %%=Orders.OrderId, the value of dataSourceName should be "Orders". The string passed must begin with a letter.

property

The [DataBindingProperties](#) object which contains information about how the data should be bound to the template. property Must be specified, but the DataBindingProperties need not be set beforehand. To bind data to a template with the default DataBindingProperties, pass in ExcelTemplate.CreateDataBindingProperties() as the property value. Otherwise, use the ExcelTemplate.CreateDataBindingProperties() method to generate a new DataBindingProperties object and set the [DataBindingProperties.MaxRows](#), [DataBindingProperties.Transpose](#), and/or [DataBindingProperties.WorksheetName](#) properties for the workbook.

Exceptions

ArgumentNullException

BindRowData will throw this exception if null (C#) or Nothing (VB.NET) is passed to the method.

ArgumentException

Remarks

Only the first row of the DataSet will be used. This method is commonly used to create a set of key-value pairs via a single row of data.

You can set several data sources for a single template. Use the following methods to set template data sources: [BindCellData](#), [BindColumnData](#), [BindRowData](#), and [BindData](#).

Examples

C#

```
ExcelTemplate xlt = new ExcelTemplate();
    xlt.Open(@"C:\ExcelWriter\EmployeeOrdersTemplate.xls");

    ///--- Bind the DataSet to the
    ///--- %=Orders.[Field] data marker.
    xlt.BindRowData(OrdersDS,
        "Orders",
        xlt.CreateDataBindingProperties());
    xlt.Process();
    xlt.Save(Page.Response, "EmployeeOrders.xls", false);
```

vb.net

```
Dim xlt As New ExcelTemplate()
    xlt.Open("C:\ExcelWriter\EmployeeOrdersTemplate.xls")

    '--- Bind the DataSet to the
    '--- %=Orders.[Field] data marker.
    xlt.BindRowData(OrdersDS, _
        "Orders", _
        xlt.CreateDataBindingProperties())
    xlt.Process()
    xlt.Save(Page.Response, "EmployeeOrders.xls", False)
```