

# HTMLToWord.HTMLInsertProperties

## Description

The [HTMLInsertProperties](#) object is a container for properties that control the behavior of HTMLToWord. You can control how HTMLToWord handles HTML tags that it does not explicitly support, as well as set the default font used when inserting text into the Word document.

**C#**

```
<p> public class HTMLInsertProperties</p>
```

**vb.net**

```
<p>Public Class HTMLInsertProperties</p>
```

## Remarks

You can not create an `HTMLInsertProperties` object. You must obtain the existing object from the HTMLToWord object by getting [HTMLToWord.InsertProperties](#).

## Properties

Name	Description
<a href="#">AcceptUnknownTags</a>	Controls how unknown tags are handled. If set to false, HTMLToWord will throw an <code>HTMLToWordException</code> if it encounters a tag that it does not explicitly know how to handle. If set to true, HTMLToWord will attempt to process the tag. See the <a href="#">IncludeContentsOfUnknownTags</a> for further user-controllable behavior.
<a href="#">DefaultFont</a>	Specifies the font to use when inserting text. This property is temporarily overridden by the <code>&lt;font&gt;</code> tag in the XHTML. If this property is not set, the document's default font is used.
<a href="#">IncludeContentsOfUnknownTags</a>	Controls how the contents of unsupported tags are handled. If set to true, the contents of unsupported tags are inserted into the document as text. If set to false, the contents of unsupported tags are ignored.