SharePointIntegration.SetDataSource(WordTemplate, Microsoft.SharePoint.SPList, String)

Introduced in build 4.1.0.1379

Description

Sets a main document data source to a SharePoint List. If the specified List contains more than one row, WordWriter will use the first row as the data source.

```
C#
```

```
public static void SetDataSource(this WordTemplate template,
Microsoft.SharePoint.SPList list, string name)
```

```
vb.net
```

```
Public Shared Sub SetDataSource(ByVal template As WordTemplate, ByVal list As
Microsoft.SharePoint.SPList, ByVal name As String)
```

Parameters

template
The current ExcelTemplate which is calling SetDataSource

list
A SharePoint List to use as the data source. WordWriter will use the first row of the List as the data source.

name
Specifies the data source name for the set of merge fields.

Exceptions

ArgumentNullException
Save will throw this exception if `null` (C#) or `Nothing` (VB.NET) is passed to the method.

ArgumentException

Remarks

Each merge field in a WordWriter template must bind to a data source field/value pair. The number of merge fields in the template may not exceed the number of values in the data source. However, the number of values in the data source may be greater than the number of merge fields in the template.

This method may be called once for each set of merge fields in the main document.

⚠ This is an extension method for the WordTemplate object to be used for binding SharePoint data to applications from within SharePoint. To use this method, you must add a reference to SoftArtisans.OfficeWriter.WordWriter.SharePointIntegration.dll

Examples

C#

```
//--- Pass the SPList to SetDataSource.
oWW.SetDataSource(myList, "Employee");
```

vb.net

```
'--- Pass the SPList to SetDataSource.
oWW.SetDataSource(myList, "Employee")
```