

WordViewSettings

Description

This class is used manipulate the View settings for a document.

C#

```
public sealed class WordViewSettings
```

C#

```
Public NotInheritable Class WordViewSettings
```

Remarks

You cannot create a new [WordViewSettings](#) object. You must use the [Document.ViewSettings](#) property to retrieve WordViewSettings properties for a document.

The following sample gets the WordViewSettings object of a document.

Examples

```
WordApplication app = new WordApplication();  
Document doc = app.Open(@"C:\sample.doc");  
WordViewSettings viewSettings = doc.ViewSettings;
```

```
Dim app As New WordApplication()  
Dim doc As Document = app.Open("C:\sample.doc")  
Dim viewSettings As WordViewSettings = doc.ViewSettings
```

Properties

Name	Description
DisplayedOutlineLevels	Sets or returns an <code>int</code> object that represents the number of heading levels that will be displayed by Word in the outline view for this document. This can be set to a number between 1 and 9.
DisplayFieldResults	Sets or returns a <code>boolean</code> that represents whether Word will display field results (<code>true</code>) or just the field text itself (<code>false</code>) in a document. For example, when set to <code>true</code> you will see the full contents of a mergefield instead of just the text value inside it.
DisplayHidden	Sets or returns a <code>boolean</code> that represents whether or not Word will display hidden contents in a document. When set to <code>true</code> , Word displays text formatted as hidden with a dotted underline. When you print hidden text, the dotted underline does not appear.

DocumentView	Sets or returns a WordViewSettings.ViewType object that represents the type of view this document will be displayed in when opened by Word. Possible values: Normal, Outline, Page.
EnvelopeVisible	Sets or returns a <code>boolean</code> that represents whether or not Word will display an envelope overlay with this document (if there is one).
IncludeFooterInBorder	Sets or returns a <code>boolean</code> that represents whether or not Word will display the footer inside the page border for a document.
IncludeHeaderInBorder	Sets or returns a <code>boolean</code> that represents whether or not Word will display the header inside the page border for a document.
ShadeFormFields	Sets or returns a <code>boolean</code> that represents whether or not Word will shade form fields in a document.
Zoom	Sets or returns a WordViewSettings.ZoomType object that represents the zoom type the document will be displayed with when opened by Word. Possible values: None, FullPage, PageWidth).
ZoomPercentage	Sets or returns an <code>int</code> that represents the zoom percentage this document will be displayed with when opened by Word. Possible values: Normal, Outline, Page.

Nested Classes

Name	Description
ViewType	View types (modes) in Word for a document.
ZoomType	Zoom types (modes) in Word for a document.